



### Feature

- \*High performance Tester, specially designed for Linear IC
- \*Automatically search unknown IC number
- \*Provide Self-Diagnosis function
- \*Equipped with loop function, able to continuous test cycle for unstable IC
- \*Programmable test voltage :0.1 to 25 voltage/250mA current limit
- \*LCD display: 20 x 2
- \*LED indicator: (1)heart(2)warning(3)pass/fail
- \*Test pins: 8 to 16-pin
- \*Test Vcc:adjustable from 5V

### Standard Accessories

- \* main unit
- \* AC cable
- \* operation manual

### Electronical Requirements

- \* Operation Voltage: AC110V/220V+/-0%
- \* Frequency Range:40 to 60 Hz

### Physical & Environmental Specifications

- \* Dimension:39cm X34cm X10.5cm
- \* Weight:3.5kgs
- \* Temperature:+5C to +45C
- \* Humidity:to 90% noncondensing
- \* Altitude:to 5000m

### DEVICE SUPPORT

OP AMP							
101	201	301	107	207	741	748	
1741	777	1741	3105	3152	3193	3420	
3493	6741	4558	353	060	061	071	
070	080	081	3008	3010	3015	3016	
3029	3030	3037	3038	3100	3130	3140	
351	3161	022	082	062	072	083	
158	258	358	01	148	149	248	
348	349	124	224	324	380	319	
COMPARATE							
139	239	339	111	211	311	3098	
3099	3290	709	2901				
REGULATED							
497	723	1524	2524	3524	3085		
TIMER							
555	556						
PERIPHERAL INTERFACE							
2003	2004						
ZENER DIODE							
.2							
78XX							
7802	7805	7806	7808	7809	7810		
7812	7815	7818	7820	7822	7824	78..	
PHOTO							
PC817	6N135	6N136	6N137				
OP18137	6N138	6N139	CNY74-2	CNY74-4			
6	TIL111	TIL112	TIL113	TIL114			
TIL115	TIL116	TIL117	TIL119	TIL124			
TIL125	TIL126	TIL127	TIL128	TIL153			
TIL154	TIL155	TIL156	TIL157				
4N25	4N26	4N27	4N28	4N29	4N30	4N31	4N32
4N33	4N34	4N35	4N36	4N37	4N38	4N39	4N28
H11A1	H11A2	H11A3	H11A4	H11A5			
H11A520	H11A550	H11B1	H11B2	H11B255			
MCT2	MCT26	MCT271	MCT272	MCT273			
MCT274	MCT275	PC827	PC837	PC847			
COMMUNICATION							
1488	1489						